| 4.0m HELIOS | HADE CAS | SETTE | interactive order form |
|--|-------------------------|--|--|
| Order number | Requested delivery date | Fabric range | Fabric colour/code |
| | | | ▶ |
| Client reference Company DELIVERY PICK UP Delivery address (Business address only) | | Valance STRAIGHT VALANCE OPTIONAL VARIO-VALANCE* Vario-Valance fabric (Soltis fabric only) Crank side LH RH Powdercoat | Control options Hirschman connector Remote control Sensor |
| | | Colour | |
| | | Code | If crank operated Crank size |
| City | State Postcode | Fixing | |
| | | Wall sealing profile | Awning pitch (Between 5-40° 14° is standard) |

Measurements - Make size only screws will be instal

Please indicate in notes section if awning/s will be in a high wind area or roof mounted. Hood securing screws will be installed during manufacturing for these awnings (Please tick to confirm reading this note.) Cassette maximum projection is 4.0m | The standard number of brackets supplied is for installation to concrete, fixing to other surfaces may require extra brackets to be ordered.

* Vario-Valance option only available on awnings with a projection of up to 3.5amd min 10° pitch required. | Vario-Valance fabric – choose from Soltis range only | When ordering a Vario-Valance, the finished awning width becomes 18mm wider than normal due to additional endcap size (e.g. 5,000mm awning will be 5,018mm overall with VV). Please allow for this.

| Qty | Reference | Width (mm) | Projection (m) | Control side | Notes |
|-----|-----------|---------------|-------------------|--------------|-------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |



Please check your order confirmation email. If you do not recieve one within 48 hours, please contact us.

Name of authorised person

Order date

Please tick this box to confirm that you are authorised to place this order.



Helioscreen Australia P/L Head Office: 32 Wattle Road, Brookvale NSW 2100 P: 02 8426 1300 F: 02 9453 0744 E: enquiries@helioscreen.com.au