

HM 80 00 STAINLESS

MOTORISED EXTERNAL ROLLER BLIND

The Helioscreen **HM 80 00 STAINLESS** is an external blind system built for durability and performance in the uniquely harsh Australian climate.

Designed and engineered in Europe, this is an uncompromising product of the highest quality, featuring marine grade stainless steel fixing brackets / cable guides, or two-piece architectural grade aluminium channels.

SYSTEM SPECIFICATIONS

Minimum width	800mm
Maximum width	6000mm
Maximum drop	4000mm
Maximum area	16sqm
Linkable	Yes
Headbox	No
Fabric deductions	37mm per side with cable guides 40mm per side with channel guides
Operation	RTS motor (remote control) or WT motor (switch)

TECHNICAL INFORMATION

Roller tube	80 / 85 / 95mm galvanised steel
Guide cables	316 grade stainless steel guide cables and fixings
Guide channels	Two part extruded guide channels 35x50mm
Installation options	Top, face, reveal with standard or reverse roll

System details

HM 80 with HMX baserail



Top fix | Face fix | Reverse roll



Minimum recess dimensions
= 140mm (w) x 150mm (h)
(drawing not to scale)

Channel & baserail sizes



Baserail | Double baserail* | Guide channels

* Double baserail used for narrow widths over 1:2.5 height

Cable guide fixings

A. S/steel bush
S/steel wall bracket

B. S/steel bush
S/steel bottom fix plate

C. S/steel bush
S/steel universal bracket

D. S/steel timber deck mount



Dimensions: A: 80 (h), 25 (w), 40(p) | B: 15 (h), 40 (w), 20 (d) | C: 30 (h), 40 (w), 40 (d) | D: 19.5 (w), 38 (h)

Cable fixing options

Front view – side-by-side & linked



A



B
(not recommended to use "B" at Link on Tiled Flooring)



C (not possible to use "C" at Link due to width of the fixing)



D

Cable side details



Face fix "L" bracket adjustment sizes



Side channel fixing options





helioscreen®

Helioscreen Australia P/L **Head Office:** 32 Wattle Road, Brookvale NSW 2100
P: 02 8426 1300 **F:** 02 9453 0744 **E:** enquiries@helioscreen.com.au
www.helioscreen.com.au